

Technical sheet

Document No. TL-044/2025-06	Issue: 2	Date of revision: 26.06.2025.
-----------------------------	----------	-------------------------------

BT-Trendi

Highly pigmented liquid tinting agent

**Field of application**

It is intended for tinting BT-Trendpol, BHBoja and other similar dispersion paints for interior use.
Not suitable for tinting silicate, silicone and lime paints.

Characteristics

- It can be easily homogenized into all dispersion paints
- Different shades can be mixed in all proportions
- Possibility of intermixing several different BT-Trendi tones

Composition

Aqueous solution of pigments and additives

Technical data

Packaging type	plastic bottle
Quantity per package	100 ml
Physical state	liquid
Color	misc
pH value	~9,25
Density	1,1 g/cm ³
Dry matter content	12-25%

Technical sheet

Document No. TL-044/2025-06	Issue: 2	Date of revision: 26.06.2025.
-----------------------------	----------	-------------------------------

Preparation and installation of materials

Before use, the bottle of BT-Trendi should be shaken well in order to completely homogenize the product. Mix the appropriate amount of pigment, depending on the desired shade, into the dispersion paint with an electric mixer or by hand. When a completely uniform mixture is achieved, the paint is ready to be applied. To prepare the desired shade, it is possible to mix several different tones of BT-Trendi. Store the rest of the product in a tightly closed bottle for later use.

Cleaning tools

Immediately after completion of the work, hand tools should be washed with clean water. Hardened residues of liquid material should be disposed of as construction waste in accordance with legal regulations.

Handling of waste

Prevent uncontrolled discharge of material into drains and watercourses. Do not mix hardened residues with municipal waste, but dispose of them as construction waste in accordance with applicable local/regional legal provisions.

Protection at work

Follow general instructions and regulations on occupational safety during construction work.
When performing work, wear adequate work clothes that ensure that the material does not come into contact with the skin.
Hand protection: protective impermeable gloves.
Eye protection: safety glasses with side protection.
For more information, see the product safety data sheet.

Technical sheet

Document No. TL-044/2025-06	Issue: 2	Date of revision: 26.06.2025.
-----------------------------	----------	-------------------------------

Storage and transport conditions

Store in dry and well-ventilated areas. Do not expose to high temperatures (>25°C) or low temperatures (<0°C).

During transportation, it is necessary to secure the product so that it does not move on the pallet, and that it is not directly affected by the sun and moisture.

Keep out of reach of children and away from food and drink.

Expiry date

Originally sealed and stored as recommended, the product has a shelf life of at least 12 months.

Quality control

Testing and monitoring of product quality is carried out daily in the internal BT laboratory and periodically in authorized institutes and laboratories.

General notes

The technical instructions are based on our previous experience, with the aim of achieving optimal results when using the product.

The above data in themselves do not create any legal obligation and do not relieve the buyer of the responsibility to perform a prior test of the suitability of the material for a specific purpose.

If the contractor notices or suspects any functional or aesthetic defect in the product during the installation of the purchased material, he is obliged, in accordance with construction practice, to stop further installation of the product in order to minimize any potential damage. He is also obliged to immediately file a complaint with the manufacturer, who will process the complaint as soon as possible.

Damage caused by incorrect product selection, improper use (failure to follow the instructions specified in this technical sheet) or unprofessional work cannot be the subject of a complaint.

This data sheet supersedes all previous editions. We reserve the right to any subsequent changes and additions.